



alocitsystems

**SAFETY DATA SHEET
ALOCIT 28.15 TROPICAL GREY RAL7004**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ALOCIT 28.15 TROPICAL GREY RAL7004

Product number AS29460B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses EPOXY COATING

1.3. Details of the supplier of the safety data sheet

Supplier ALOCIT USA
3169 S. Arlington Ave., Indianapolis, Indiana 46203.
+1 317 631-9100
ALOCIT INTERNATIONAL
3 Charles Wood Road, Dereham, UK NR19 1SX
+44 1362 694915

1.4. Emergency telephone number

Emergency telephone 24 HR EMERGENCY TELEPHONE NUMBER : US +1 800 535 5053 UK + 44 (0) 7930 595916

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Human health The liquid is irritating to eyes and skin.

Environmental The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

ALOCIT 28.15 TROPICAL GREY RAL7004

| | |
|---------------------------------|---|
| Precautionary statements | <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> |
|---------------------------------|---|

| | |
|---------------------------------------|---|
| Supplemental label information | EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
|---------------------------------------|---|

| | |
|-----------------|---|
| Contains | bis-[4-(2,3-epoxipropoxy)phenyl]propane, Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700, FATTY ACIDS, C18, UNSATD., DIMERS, REACTION PRODUCT WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE |
|-----------------|---|

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current UK criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|---|----------------------|
| reaction product: bisphenol-A-(epichlorhydrin) | 30-60% |
| CAS number: 25068-38-6 | EC number: 500-033-5 |
| Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411 | |
| BARIUM SULPHATE | 30-60% |
| CAS number: 7727-43-7 | EC number: 231-784-4 |
| Classification Not Classified | |
| TITANIUM DIOXIDE | 10-30% |
| CAS number: 13463-67-7 | EC number: 236-675-5 |
| Classification Not Classified | |

ALOCIT 28.15 TROPICAL GREY RAL7004

| | |
|--|----------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | <1% |
| CAS number: 1675-54-3 | EC number: 216-823-5 |
| Classification | |
| Skin Irrit. 2 - H315 | |
| Eye Irrit. 2 - H319 | |
| Skin Sens. 1 - H317 | |
| Aquatic Chronic 2 - H411 | |
| Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700 | <1% |
| CAS number: 9003-36-5 | EC number: 500-006-8 |
| Classification | |
| Skin Irrit. 2 - H315 | |
| Skin Sens. 1 - H317 | |
| Aquatic Chronic 2 - H411 | |
| Natural Calcium Carbonate | <1% |
| CAS number: 1317-65-3 | EC number: 215-279-6 |
| Classification | |
| Not Classified | |
| FATTY ACIDS, C18, UNSATD., DIMERS, REACTION PRODUCT WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE | <1% |
| CAS number: 162627-17-0 | EC number: 605-296-0 |
| Classification | |
| Skin Sens. 1A - H317 | |
| 1-METHOXY-2-PROPANOL | <1% |
| CAS number: 107-98-2 | EC number: 203-539-1 |
| Classification | |
| Flam. Liq. 3 - H226 | |
| STOT SE 3 - H336 | |
| CYCLOHEXANONE | <1% |
| CAS number: 108-94-1 | EC number: 203-631-1 |
| Classification | |
| Flam. Liq. 3 - H226 | |
| Acute Tox. 4 - H332 | |

ALOCIT 28.15 TROPICAL GREY RAL7004

| | |
|---|----------------------|
| Solvent naphtha (petroleum), light arom. | <1% |
| CAS number: 64742-95-6 | EC number: 918-668-5 |
| Classification | |
| Muta. 1B - H340 | |
| Carc. 1B - H350 | |
| Asp. Tox. 1 - H304 | |

The full text for all hazard statements is displayed in Section 16.

Composition comments This mixture contains $\geq 1\%$ Titanium Dioxide (CAS 13463-67-7) The Annex VI classification of Titanium Dioxide does not apply to this mixture according to its Note 10.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------|--|
| Inhalation | Move affected person to fresh air at once. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately. |
| Ingestion | Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention immediately. |
| Skin contact | Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues. |
| Eye contact | Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention promptly if symptoms occur after washing. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|---------------------|---|
| Inhalation | No specific symptoms known. |
| Ingestion | No specific symptoms known. |
| Skin contact | Prolonged skin contact may cause redness and irritation. |
| Eye contact | Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. |

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|---------------------------------------|--|
| Suitable extinguishing media | Water. Foam. Carbon dioxide (CO ₂). Dry chemicals, sand, dolomite etc. |
| Unsuitable extinguishing media | Not known. |

5.2. Special hazards arising from the substance or mixture

Specific hazards Fire or high temperatures create: Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO). Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

ALOCIT 28.15 TROPICAL GREY RAL7004

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide (CO). Halogenated hydrocarbons.

5.3. Advice for firefighters

Protective actions during firefighting Isolate area. Very toxic to aquatic organisms. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Keep unnecessary and unprotected personnel from entering the area. Avoid inhalation of vapours. Isolate area.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Do not eat, drink or smoke when using this product. Persons susceptible to allergic reactions should not handle this product. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray/mists. Store in tightly-closed, original container. Wear suitable protective clothing as protection against splashing or contamination.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BARIUM SULPHATE

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): 10 mg/m³ inhalable dust

TITANIUM DIOXIDE

ALOCIT 28.15 TROPICAL GREY RAL7004

EH40 WEL, Time Weighted Average (TWA):, Inhalable dust. 10 mg/m³, 8 h
 EH40 WEL, Time Weighted Average (TWA):, Respirable dust. 4 mg/m³, 8 h

Natural Calcium Carbonate

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust
 Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³
 Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³
 Sk

CYCLOHEXANONE

Long-term exposure limit (8-hour TWA): WEL 10 ppm(Sk)
 Short-term exposure limit (15-minute): WEL 20 ppm(Sk)

Solvent naphtha (petroleum), light arom.

Long-term exposure limit (8-hour TWA): SUP 25 ppm 100 mg/m³
 Short-term exposure limit (15-minute): SUP No std. No std.

WEL = Workplace Exposure Limit.
 Sk = Can be absorbed through skin.

reaction product: bisphenol-A-(epichlorhydrin) (CAS: 25068-38-6)

| | |
|-------------|--|
| DNEL | Industry - Dermal; Short term systemic effects: 8.3 mg/kg/day Industry - Inhalation; Short term systemic effects: 12.3 mg/m ³ Industry - Dermal; Long term systemic effects: 8.3 mg/kg/day Industry - Inhalation; Long term systemic effects: 12.3 mg/m ³ Consumer - Dermal; Short term systemic effects: 3.6 mg/kg/day Consumer - Inhalation; Short term systemic effects: 0.75 mg/m ³ Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day Consumer - Dermal; Long term systemic effects: 3.6 mg/kg/day Consumer - Inhalation; Long term systemic effects: 0.75 mg/m ³ |
| PNEC | - Fresh water; 3 mg/l - marine water; 0.3 mg/l - Sediment (Freshwater); 0.5 mg/kg - Sediment (Marinewater); 0.5 mg/kg - Intermittent release; 0.013 mg/l |

BARIUM SULPHATE (CAS: 7727-43-7)

| | |
|-------------|--|
| DNEL | Workers - Inhalation; Long term systemic effects: 10 mg/m ³ Workers - Inhalation; Long term local effects: 10 mg/m ³ Consumer - Inhalation; Long term systemic effects: 10 mg/m ³ Consumer - Oral; Long term systemic effects: 13000 mg/kg |
| PNEC | Fresh water; 115 µg/l STP; 62.2 mg/l Sediment (Freshwater); 600.4 mg/kg Soil; 207.7 mg/kg |

TITANIUM DIOXIDE (CAS: 13463-67-7)

| | |
|-------------|---|
| DNEL | Workers - Inhalation; Long term local effects: 10 mg/m ³ Professional - Inhalation; Long term local effects: 10 mg/m ³ Consumer - Oral; Long term systemic effects: 700 mg/kg/day |
|-------------|---|

ALOCIT 28.15 TROPICAL GREY RAL7004

PNEC marine water; 0.0184 mg/l
 Fresh water; 0.184 mg/l
 Intermittent release; 0.193 mg/l
 STP; 100 mg/l
 Sediment, marine water; 100 mg/kg
 Sediment, Fresh water; 1000 mg/kg
 Soil; 100 mg/kg

bis-[4-(2,3-epoxipropoxy)phenyl]propane (CAS: 1675-54-3)

DNEL Workers - Dermal; Short term systemic effects: 8.3 mg/kg, bw/day
 Workers - Inhalation; Short term systemic effects: 12.3 mg/m³
 Workers - Dermal; Long term systemic effects: 8.3 mg/kg, bw/day
 Workers - Inhalation; Long term systemic effects: 12.3 mg/m³
 General population - Dermal; Short term systemic effects: 3.6 mg/kg, bw/day
 General population - Inhalation; Short term systemic effects: 0.75 mg/m³
 General population - Oral; Short term systemic effects: 0.75 mg/kg, bw/day
 General population - Dermal; Long term systemic effects: 3.6 mg/kg, bw/day
 General population - Inhalation; Long term systemic effects: 0.75 mg/m³
 General population - Oral; Long term systemic effects: 0.75 mg/kg, bw/day

PNEC Fresh water; 3 µg/l
 marine water; 0.3 µg/l
 STP; 10 mg/l
 Sediment (Freshwater); 0.5 mg/kg
 Sediment (Marinewater); 0.5 mg/kg
 Sediment; 0.05 mg/kg
 Intermittent release; 0.013 mg/l

BENTONE SD3 (CAS: 121888-67-3)

Ingredient comments No exposure limits known for ingredient(s).

Formaldehyde, polymer with (chloromethyl)oxirane and phenol, mw <=700 (CAS: 9003-36-5)

DNEL Industry - Dermal; Short term local effects: 8.3 ppm
 Industry - Dermal; Long term systemic effects: 104.15 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 29.39 mg/m³
 Consumer - Dermal; Long term systemic effects: 62.5 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 8.7 mg/m³
 Consumer - Oral; Long term systemic effects: 6.25 mg/kg/day

PNEC - Fresh water; 0.003 mg/l
 - marine water; 0.0003 mg/l
 - Sediment (Freshwater); 0.294 mg/kg
 - Sediment (Marinewater); 0.0294 mg/kg
 - Soil; 0.237 mg/kg
 - Intermittent release; 0.0254

Trimethylolpropane (CAS: 77-99-6)

DNEL Workers - Inhalation; Long term systemic effects: 3.3 mg/m³
 Workers - Dermal; Long term systemic effects: 0.94 mg/kg
 Consumer - Inhalation; Long term systemic effects: 0.58 mg/m³
 Consumer - Dermal; Long term systemic effects: 0.34 mg/kg
 Consumer - Oral; Long term systemic effects: 0.34 mg/kg

ALOCIT 28.15 TROPICAL GREY RAL7004

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

| | |
|----------------------------|--|
| Ingredient comments | WEL = Workplace Exposure Limits |
| DNEL | Industry - Inhalation; Short term : 553.5 mg/m ³ Industry - Inhalation; Long term : 369 mg/m ³ Industry - Dermal; Long term : 50.6 mg/m ³ Consumer - Inhalation; Long term : 43.9 mg/m ³ Consumer - Dermal; Long term : 18.1 mg/m ³ Consumer - Oral; Long term : 3.3 mg/m ³ |
| PNEC | - Fresh water; 10 mg/l - Sediment; 41.6 mg/kg - Soil; 2.47 mg/kg - STP; 100 mg/l |

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (CAS: 68609-97-2)

| | |
|-------------|---|
| DNEL | Workers - Inhalation; Long term systemic effects: 3.6 mg/m ³ Workers - Dermal; Long term systemic effects: 1 mg/kg/day General population - Inhalation; Long term systemic effects: 0.87 mg/m ³ General population - Dermal; Long term systemic effects: 0.5 mg/kg/day General population - Oral; Long term systemic effects: 0.5 mg/kg/day |
| PNEC | Fresh water; 0.106 mg/l Fresh water, Intermittent release; 0.072 mg/l marine water; 0.011 mg/l STP; 10 mg/l Sediment (Freshwater), dw; 307.16 mg/kg Sediment (Marinewater), dw; 30.72 mg/kg Soil, dw; 1.234 mg/kg |

Solvent naphtha (petroleum), light arom. (CAS: 64742-95-6)

| | |
|-------------|--|
| DNEL | Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m ³ Consumer - Inhalation; Long term systemic effects: 32 mg/m ³ Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Oral; Long term systemic effects: 11 mg/kg/day |
|-------------|--|

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

ALOCIT 28.15 TROPICAL GREY RAL7004

| | |
|--|--|
| Other skin and body protection | AVOID ALL SKIN AND RESPIRATORY CONTACT! Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact. |
| Hygiene measures | Provide eyewash station. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product. |
| Respiratory protection | If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly. |
| Environmental exposure controls | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------------------|
| Appearance | Coloured paste. or Liquid. |
| Colour | Variable |
| Odour | Slight. |
| Odour threshold | No information available. |
| pH | No information available. |
| Melting point | Not determined. |
| Initial boiling point and range | Not determined. |
| Flash point | >1500°C |
| Evaporation rate | Not determined. |
| Evaporation factor | No information available. |
| Flammability (solid, gas) | No information available. |
| Upper/lower flammability or explosive limits | Not determined. |
| Other flammability | No information available. |
| Vapour pressure | Not determined. |
| Vapour density | Not determined. |
| Relative density | No information available. |
| Bulk density | No information available. |
| Solubility(ies) | No information available. |
| Partition coefficient | No information available. |
| Auto-ignition temperature | No information available. |
| Decomposition Temperature | No information available. |
| Viscosity | Not determined. |
| Explosive properties | No information available. |
| Explosive under the influence of a flame | Not considered to be explosive. |

ALOCIT 28.15 TROPICAL GREY RAL7004

Oxidising properties Not available.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Hazardous reactions or instability may occur under certain conditions of storage or use.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:
Strong oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapour may irritate respiratory system/lungs.

Ingestion Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritation of eyes and mucous membranes.

Toxicological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 15,000.0

Species Rat

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 23,032.0

Species Rabbit

ATE dermal (mg/kg) 23,032.0

ALOCIT 28.15 TROPICAL GREY RAL7004

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not applicable.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Skin sensitisation

Skin sensitisation Irritating to skin. Prolonged skin contact may cause redness and irritation. May cause sensitisation by skin contact.

Carcinogenicity

Carcinogenicity Not applicable.

Reproductive toxicity

Reproductive toxicity - fertility Fertility - NOAEL 750 mg/kg/day, Oral, Rat

Reproductive toxicity - development Developmental toxicity: - NOAEL: 180 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure Not applicable.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not applicable.

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 11400 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes eye irritation.

Respiratory sensitisation

Respiratory sensitisation May cause sensitisation or allergic reactions in sensitive individuals.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

ALOCIT 28.15 TROPICAL GREY RAL7004

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

FATTY ACIDS, C18, UNSATD., DIMERS, REACTION PRODUCT WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE

Toxicological effects No information available.

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >10000 mg/kg, Oral, Rat

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Reproductive toxicity

Reproductive toxicity - fertility Fertility - NOAEL >1000 mg/kg, Oral, Rat F1

SECTION 12: Ecological information

Ecotoxicity Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.

Ecological information on ingredients.

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Ecotoxicity Toxic to aquatic life.

12.1. Toxicity

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Acute aquatic toxicity

Acute toxicity - fish EC₅₀, 96 hours: 3.6 mg/l, Oncorhynchus mykiss (Rainbow trout)

ALOCIT 28.15 TROPICAL GREY RAL7004

| | |
|---|---|
| Acute toxicity - aquatic invertebrates | EC ₅₀ , 48 hours: 1.8 mg/l, Daphnia magna |
| Acute toxicity - aquatic plants | EC ₅₀ , 72 hours: 11 mg/l, Scenedesmus subspicatus |
| <u>Chronic aquatic toxicity</u> | |
| Chronic toxicity - fish early life stage | Not available. |
| Chronic toxicity - aquatic invertebrates | Not available. |

bis-[4-(2,3-epoxipropoxy)phenyl]propane

| | |
|---|--|
| Toxicity | WGK 2 |
| <u>Acute aquatic toxicity</u> | |
| Acute toxicity - fish | LC ₅₀ , 96 hours: 1.3 mg/l, Fish |
| Acute toxicity - aquatic invertebrates | EC ₅₀ , 48 hours: 2.1 mg/l, Ceriodaphnia dubia (water flea) |
| Acute toxicity - aquatic plants | EC ₅₀ , 72 hours: 11 mg/l, Algae |

FATTY ACIDS, C18, UNSATD., DIMERS, REACTION PRODUCT WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE

| | |
|---|--|
| <u>Acute aquatic toxicity</u> | |
| Acute toxicity - fish | LD ₅₀ , 48 hours: >150 mg/l, Leuciscus idus (Golden orfe) |
| Acute toxicity - aquatic invertebrates | EL50, 48 hours: >100 mg/l, Daphnia magna |
| Acute toxicity - aquatic plants | ErL50, 72 hours: >100 mg/l, Pseudokirchneriella subcapitata |
| Acute toxicity - microorganisms | IC ₅₀ , 16 hours: >430 mg/l, Pseudomonas putida |
| <u>Chronic aquatic toxicity</u> | |
| Chronic toxicity - aquatic invertebrates | EL50, 21 days: >100 mg/l, Daphnia magna |

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

| | |
|--------------------------------------|----------------------------|
| Persistence and degradability | Not readily biodegradable. |
|--------------------------------------|----------------------------|

bis-[4-(2,3-epoxipropoxy)phenyl]propane

| | |
|-----------------------|----------------------------|
| Biodegradation | Not readily biodegradable. |
|-----------------------|----------------------------|

ALOCIT 28.15 TROPICAL GREY RAL7004

FATTY ACIDS, C18, UNSATD., DIMERS, REACTION PRODUCT WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE

Persistence and degradability Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 3.242

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Bioaccumulative potential log Pow: 2.65 - 3.78, BCF: 3 - 31 31.00,

12.4. Mobility in soil

Mobility No data available.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Mobility No data available.

Surface tension 60 mN/m @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects Not known.

Ecological information on ingredients.

reaction product: bisphenol-A-(epichlorhydrin)

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

ALOCIT 28.15 TROPICAL GREY RAL7004

| | |
|-------------------------|--|
| Disposal methods | Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Avoid the spillage or runoff entering drains, sewers or watercourses. |
| Waste class | EWC NUMBER : Allocation of a waste code number in accordance with the European Waste Catalogue, should be carried out in agreement with an EA authorised waste disposal company. |

SECTION 14: Transport information

| | |
|-----------------------------|---|
| Road transport notes | SP375 – These substances when carried in Single or Combination packaging's containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any provisions of ADR provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 |
| Sea transport notes | Chapter 2.10 – 2.10.2.7 – Marine Pollutants packaged in Single or Combination packaging's containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any other provisions of this code relevant to Marine Pollutants, provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of Marine Pollutants also meeting the Criteria for inclusion in another class, all provisions of this code relevant to any additional hazards continue to apply |
| Air transport notes | A197 - These substances when carried in Single or Combination packaging's containing a net Qty per single or inner packaging of 5ltr or less for liquids or having a net mass per single or inner packaging of 5kg or less for solids, are not subject to any other provisions of these regulations provided the packaging's meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8 |

14.1. UN number

| | |
|-------------------------|------|
| UN No. (ADR/RID) | 3082 |
| UN No. (IMDG) | 3082 |
| UN No. (ICAO) | 3082 |

14.2. UN proper shipping name

| | |
|---------------------------------------|---|
| Proper shipping name (ADR/RID) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A) |
| Proper shipping name (IMDG) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A) |
| Proper shipping name (ICAO) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A) |
| Proper shipping name (ADN) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A) |

14.3. Transport hazard class(es)

| | |
|----------------------------|---|
| ADR/RID class | 9 |
| ADR/RID label | 9 |
| IMDG class | 9 |
| ICAO class/division | 9 |

Transport labels



ALOCIT 28.15 TROPICAL GREY RAL7004

14.4. Packing group

| | |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group | III |
| ICAO packing group | III |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

| | |
|--|----------|
| EmS | F-A, S-F |
| Emergency Action Code | •3Z |
| Hazard Identification Number (ADR/RID) | 90 |
| Tunnel restriction code | (E) |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-----------------------------|---|
| National regulations | Control of Substances Hazardous to Health Regulations 2002 (as amended). |
| EU legislation | Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. |
| Guidance | A guide to local exhaust ventilation (LEV) HSG258 (as amended) Workplace Exposure Limits EH40. |

15.2. Chemical safety assessment

Not applicable.

SECTION 16: Other information

| | |
|-----------------|------------|
| Revision date | 09/08/2024 |
| Revision | 17 |
| Supersedes date | 22/06/2022 |

ALOCIT 28.15 TROPICAL GREY RAL7004

Hazard statements in full

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

The information contained within this document is presented in good faith and is believed to be correct. Alocit International Limited makes no representation as to the accuracy and/or completeness of this information. This information is issued on the condition that the user will determine the safety and suitability of products for their purposes prior to use. All technical details and values presented are deemed typical and do not constitute a delivery specification.